

538,461

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 July 2004 (01.07.2004)


PCT

(10) International Publication Number  
**WO 2004/054919 A1**

- (51) International Patent Classification<sup>7</sup>: **B66B 21/00** (72) Inventor: **OSTERMEIER, Jörg** (deceased).
- (21) International Application Number: **PCT/US2003/003801** (72) Inventor; and  
(75) Inventor/Applicant (for US only): **MEYER, Helmut** [DE/DE]; Plettenbergstrasse 8, 31675 Buckeburg (DE).
- (22) International Filing Date: 7 February 2003 (07.02.2003) (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (26) Publication Language: English
- (30) Priority Data:  
PCT/US02/39945  
13 December 2002 (13.12.2002) US
- (71) Applicant (for all designated States except US): **OTIS ELEVATOR COMPANY** [US/US]; Ten Farm Springs Road, Farmington, CT 06032 (US).
- (71) Applicants (for US only): **ENGEL ROJAHN, Heike, Helene** (legal representative of the deceased inventor) [DE/DE]; Kiesweg 32, 31675 Buckeburg (DE). **OSTERMEIER, Helene** (legal representative of the deceased inventor) [DE/DE]; Kiesweg 30, 31675 Buckeburg (DE).
- Declaration under Rule 4.17:  
— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: STEPCHAIN LINK FOR A PASSENGER CONVEYOR SYSTEM



(57) Abstract: A stepchain for a passenger conveyor includes a plurality of stepchain links (30, 130, 230). There is only one link-to-link interface (31) on each side of the steps (24) such that the number of links (30) on each side of the steps (24) is equal to the number of steps (24). The inventive arrangement reduces rotation or contraction of the stepchain between steps (24). Elongation of the stepchain is also reduced as there is a reduction in the number of interfaces (31). The inventive arrangement also facilitates arcuate movement of the steps (24) along a constant radius through the transition zones between the inclined area (27) and the landing areas (29). Having a truly arcuate movement allows for reducing the gap (33) between the steps (24) at the transition zones. In one example at least one needle bearing (190) is associated with an attachment mechanism (184, 284) at the interface (31) between adjacent links (30) to allow for rotation between the stepchain links (30) and to eliminate the need for lubrication.

WO 2004/054919 A1

**WO 2004/054919 A1**



**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*